	Sail measurement form Furling mainsail				
	Fill in and send to <u>cotes@sailonet.com</u>				
Sailonet	Radial	Date: Cut : Dacron Elex Cut (Laminate) DCX clo Cut Pro Radial White	(option)		
Type of boat:	C	compulsory Marina:	C	Dock:	
Last name:		First Name :	Pł	none:	
Brand of furler:					
Sailing programm: Inshore cruising Cruising/racing Racing Offshore cruising					
Mast furler	Boom furler	Choice uv-prote	ection clew		
Fill in the form in corresponden	ce with your equipment	Furling Su	nbrella	/	
	cm	Marine Blue 5031			Halyard max hoisted
2 3	cm	Natural Si	ilver		
3	mm	5020 50	035		
(4)			026		
5 cm		Same colour for uv-protection,	leech and foot. Please		
6 A B		contact us for furth			
		Comments	>		
8 cm	cm				
6	System	n clew			Top of the tackshakle
				/ / Before pointing, put	Top c tacks
	(A)		Mark	/ car max back	
6					
Axis of the					
	C			(2)	tackshakle
The outhaul is running throug is fixed on the car.The car car certain part of the boom.	i only move on a		←(8)	/	
,					r+1
				Height of gr	oove
/	B		tre of sail's luff	onening	5
	î))	↑)
The clew is lashed on the car. the entire length of the boom.	The car is moving on				*
		🕛 📋 🤍 Gro	ove opening w	idth	