
Sparcraft offers a new range of bowsprits. Easily removed from the deck these innovative spars can be fitted on sailing boats from 25 to 57 feet. They have been specially designed for Gennakers/Code zero or asymmetric Spinnakers. The deck fixing device allows a free foredeck when arriving at the harbour or mooring.




Simple and easy functioning



Deck fixing block



 Simple installation (only a short backwards movement is needed to fit the bowsprit on the deck);



- Integrated line stopper for holding the tackline;
- The locking system incorporates an an anti-theft device.



Integrated line stopper


Complete kit including:


- Aluminium bowsprit with special end fittings: bridle attachment at the front and fixing block device at the back (delivered pre-installed);
- Adjustable Central fixing collar;
- Deck fixing blocks.

Technical datas



Ergonomic design







fitted-in sheave

The central fixing collar is captive from the bowsprit but it is removable from the fixing block. The foredeck is therefore totally free (no more fixed collar in the way).



saction a	Total longth	Minimum length	Maximum langth	Use example	Maximum sail area (m²)	
	•	inside (mm- feet)	outside (mm)	Boat length (feet)	Asymmetric spinnaker	Gennaker & Code O
ø 70	1600 - 5'3"	800 - 2'7"	800 - 2'7"	25-36'	60	37*
ø 80	1800 - 5'10"	900 - 2'11"	900 - 2'11"	36-40'	82	52*
ø 90	1900 - 6'2"	950 - 3'1"	950 - 3'1"	40-47'	102	65*
ø 100	2000 - 6'6"	1000 - 3'3"	1000 - 3'3"	48-57'	130 / 150*	105*

Options Articulating toggle for "Parking" Deck fit-Working Stem head **Options** gennaker and Code deck fitting deck fitting ting cover fitting zero furler



The SPARCRAFT bowsprit advantages:

- Easy foredeck installation and removal;
- Automatic locking device for a maximum safety;
- Suitabe for a large range of sailboats
- For Code zero and Gennaker





Articulating toggle for Gennaker Code zero furler attachment,

www.sparcraft.com

